

- Pure sine wave inverter
- Built-in MPPT solar charge controller
- Selectable input voltage range for home appliances and personal computers
- Selectable charging current based on applications
- Configurable AC/Solar input priority via LCD setting
- Compatible to mains voltage or generator power
- Auto restart while AC is recovering
- Overload and short circuit protection
- Smart battery charger design for optimized battery performance
- Cold start function



### Axpert MKS 2KVA/3KVA Plus Inverter/Charger Specification

MODEL	Axpert MKS 2K-24 Plus	Axpert MKS 2K-48 Plus	Axpert MKS 3K-24 Plus	Axpert MKS 3K-48 Plus
Rated Power	2000VA/1600W	2000VA/1600W	3000VA/2400W	3000VA/2400W
<b>INPUT</b>				
Voltage	120 VAC or 230 VAC			
Selectable Voltage Range	95-140 VAC or 170-280 VAC (For Personal Computers) 65-140 VAC or 90-280 VAC (For Home Appliances)			
Frequency Range	50 Hz/60 Hz (Auto sensing)			
<b>OUTPUT</b>				
AC Voltage Regulation (Batt. Mode)	110/120 VAC $\pm$ 5% (User selectable) or 230VAC $\pm$ 5%			
Surge Power	4000VA		6000VA	
Efficiency (Peak)	90% - 93%			
Transfer Time	10 ms (For Personal Computers) 20 ms (For Home Appliances)			
Waveform	Pure sine wave			
<b>BATTERY &amp; AC CHARGER</b>				
Battery Voltage	24 VDC	48 VDC	24 VDC	48 VDC
Floating Charge Voltage	27 VDC	54 VDC	27 VDC	54 VDC
Overcharge Protection	31 VDC	62 VDC	31 VDC	62 VDC
Maximum Charge Current	20 A or 20 A / 30 A*	10 A or 10 A / 15 A*	20 A or 20 A / 30 A*	10 A or 10 A / 15 A*
<b>SOLAR CHARGER</b>				
Maximum PV Array Power	1500 W	3000 W	1500 W	3000 W
MPPT Range @ Operating Voltage	30~ 115 VDC or 60 ~ 115 VDC	60 ~ 115 VDC	30~ 115 VDC or 60 ~ 115 VDC	60 ~ 115 VDC
Maximum PV Array Open Circuit Voltage	145 VDC			
Maximum Charging Current	60A			
Maximum Efficiency	98%			
Standby Power Consumption	2 W			
<b>PHYSICAL</b>				
Dimension, D X W X H (mm)	140 x 295 x 479			
Net Weight (kgs)	11.5			
<b>OPERATING ENVIRONMENT</b>				
Humidity	5% to 95% Relative Humidity(Non-condensing)			
Operating Temperature	0°C to 55°C			
Storage Temperature	-15°C to 60°C			

\* There are charging current selection only available for 230VAC system.

\* Product specifications are subject to change without further notice



Address: 5F, No.151, Xinhu 1st Road, Neihu Dist., Taipei, Taiwan, R.O.C. Website: [www.voltronicpower.com](http://www.voltronicpower.com)  
TEL: 886-2-27918296 FAX: 886-2-87918216 E-mail: [sales@voltronicpower.com](mailto:sales@voltronicpower.com)

Advancing Power